

External walls	
The construction starting from the inside:	
- plasterboard 13mm	
- additional mineral wool 50mm	
- recommended additional insulation of 45x45	
mm to 600 mm	
- vapor barrier with taped connections	
- mineral wool (100+100) mm	
- frame 45x195 mm to 600 mm	
- wind protection plate, gympsum board 10 mm	
- protective mesh against rodents	
- ventilation slat 12 mm	
- sheathing 23 mm (only vertically-ribbed)	
- cladding UTV 23x95 / 125 mm,	
primer+colour (1x)	
*Cladding partially installed on elements.	
- bottom girdle (pressure impregnated) and the	
upper girdle is supplied bulk	
- the special gasket under the bottom girdle is	
supplied in bulk	
Painting	
- the supplied cladding is installed to the	
elements and covered with one layer of primer	
and paint	
- corner boards, cladding boards, eaves'	
endboards and base boards are covered with	
one layer of primer and paint	NEW PEGENATURG WITH MOVING WALLING
Dwelling Rooms' Intermediate Ceiling	NB!! BEGINNING WITH HOUSES HAVING
When supplied, accessories are loose.	1.5 FLOORS!!
The structure from top to bottom:	
- OSB plate 22 mm	
- joists according to the figures	
- mineral wool 200 mm	
- vapor barrier	
- sheathing 21x95 to 400	
- 2x gypsum board 13 mm	



Roof Structure and Accessories The accessories are supplied in bulk -gypsum board to the ceiling 13 mm - sheathing 21x90 - vapor barrier - the rafters and trusses according to the figures - underlay - airing moldings - sheathing	
Eaves' boards	
- eaves' baseboards 21x95 and endboards	
interleaved	
- eaves scaffold  * the beams visible from the side eaves are not	
spaced at regular intervals.	
* boards are supplied in bulk	
Weatherboards	
Supplied in bulk:	
- corner boards 20x125	
- distribution slats marked on the figure	
Windows and External Doors Sills	
Delivered separately:	
- door and window sills 20x120	
Windows - Windows installed, insulated and taped on the external wall elements according to the list of	
windows	
- the potential boundary moldings of the arched	1
windows are not part of the delivery	
- exterior extension boards of windows	
- exterior window ledges - the window is mounted ca 40 mm inside the	
surface of the window	
- internal slats are not part of the delivery	
- window fittings are supplied in bulk	
- window dimensions, outer dimension in both	
horizontal and vertical dimensions	
- windows are seen from the inside	



- Windows are of a white colour	
DESCRIPTION OF THE WINDOWS	
Wooden windows, opened either via tilting or	
turning, aluminium drip mold, specification	
according to the figures	
- without brooch sticks	
- NB! Thermal windows (U-value = 0,9)	
-3x package, 2x Selective + argon	
Outer doors:	
Gracia, Viljandi Aken ja Uks, ASSA 565 with	
a lock casing	
Interior doors: white interior doors, Viljandi	
Aken ja Uks	
Partition walls	
- bottom and upper girdles 42x95	
- frame 45x90	
- insulation of mineral wool 100 mm	
- gypsum board 13 mm	
- gypsum board 13 mm (with the exception of	
the attachments of scutes)	
Other accessories	
Accessories are supplied in bulk	
- corner fitting details of villas and structures	
- tilted beams of elements 50x75 and tilted	
boards 21x95	
- sauna benches as wood material, inner board	
of the steam room supplied in bulk	
Figures	
- main figures (main, façade and structural	
cross-sectional views), without explanations	
- measurement and design drawings of supplied	
structures	
- foundation drawings' dimensioned figures	
- packing list with work descriptions	
- installation instructions	